



| | |
|----------------|------|
| Catalog Number | |
| Project | Type |

FEATURES & SPECIFICATIONS

APPLICATION — The high performance luminaire is designed for retrofit applications into existing acorn style luminaires replacing traditional and less efficient light sources without compromising the quality of the delivered light.

CONSTRUCTION — The heavy duty housing is constructed of die-cast aluminum. The optical assemblies are secured in place for weather tight protection. The LED's are positioned in a manner to provide 360° uniform illumination.

ELECTRICAL SYSTEM — Available in up to a 75W configuration which provides approximately 6300 lumens of Cool White light. Auto-ranging multi-volt (100V~305V) input remote driver. THD≤12%. 0-10 PWM Input. Manually dimmable with a 250K variable resistor (provided by others). Exceptionally long life LED's and driver. Rated for >50K hours of operation. 50' max remote distance between screw-in retrofit unit and driver.

MOUNTING — The retrofit unit is designed to screw directly into an existing 4KV mogul base porcelain socket. A medium base reduced length version is available. The LED driver housing comes with universal mounting plate that allows it to be mounted where the existing HID ballast was housed (hardware provided by others).

LED Acorn Retrofit LACR SERIES



The LACR LED Acorn Retrofit System is provided by Techlight complete with LED module and a power supply module with mounting brackets to transform the existing fixture into an efficient LED unit.



ACORN LIGHT



COLONIAL POST TOP

| Series | Height | Width |
|------------------|--------|--------|
| LACR45 | 11.50" | Ø4.00" |
| LACR75 | 14.00" | Ø4.00" |
| LACR45-RL | 9.95" | Ø4.00" |
| LACR75-RL | 12.45" | Ø4.00" |

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

LACR

| Series | Wattage | Color Temp | Voltage | Options |
|-------------|--|-----------------------------|----------------------------------|---|
| LACR | 45 45W/3800 Lumens 75 75W/6300 Lumens | C Cool White (5000K) | 1 Multi-Volt ¹ | Blank Mogul Base, Standard Length RL Medium Base, Reduced Length |

Example: LACR75C1

NOTES

¹ Multi-Volt is an auto ranging power supply from 100V to 305V input.