




DRILLED PER FIXTURE REQUIREMENTS:
DM1-DRILLED FOR 1 FIXTURE
DM290 -DM2180-DRILLED FOR 2 FIXTURES AT 90° OR 180°
DM390-DM3120-DRILLED FOR 3 FIXTURES AT 90° OR 120°
D490-DRILLED FOR 4 FIXTURES



3X5 HAND HOLE
STD SIDE A

DRILLED MOUNT OPTIONS


Drilling Locations

Sides	A	B	C	D
Hand Hole	X			
DM1	X			
DM290	X	X		
DM2180		X		X
DM390	X	X	X	X
DM490	X	X	X	X

POLE DIA

POLE HEIGHT


POLE DETAIL




TENON MOUNT OPTIONS

TENON MOUNT OPTIONS:
T238-Ø 2.38OD X 4.00 LG
T278-Ø 2.88OD X 4.00 LG
T300-Ø 3.00 OD X 6.00 LG
T312-Ø 3.50 OD X 6.00 LG

TLGFIA STD MNT
12" ABOVE HH



TLGFIA STD MOUNT



Ø 1.00 x 36.00 ANCHOR BOLT
AB KIT REQ'D KAB13611R


POLE SPECIFICATIONS RSP30-5-11						
NO.	COMPONENT	ASTM SPEC	MIN. YIELD (PSI)			
1	POLE SHAFT	A500 GR C	50,000			
2	BASE PLATE	A36	36,000			
3	ANCHOR BOLTS	F1554 GR 55	55,000			
4	ANCHOR BOLT HDW	A153	---			
FINISH SPECIFICATIONS						
IF GALV FINISH OPTION IS SPECIFIED POLE WILL BE HOT DIP GALVANIZED PER ASTM A123 SPECIFICATIONS. IF GALVP FINISH OPTION IS SPECIFIED POLE WILL BE HOT DIP GALVANIZED PER ASTM A123, THEN POWDER COATED WITH TEXTURED POLYESTER POWDER COAT ELECTROSTATICALLY APPLIED.						
IF POLYESTER POWDER COAT PAINT FINISH IS SPECIFIED POLE WILL BE SHOT BLASTED, WASHED, PRETREATED & DRIED THEN POWDER COAT WILL BE ELECTROSTATICALLY APPLIED PER AAMA 2604/2605 SPECIFICATIONS.						
POLE DIMENSIONS						
POLE HGT. (FT)		POLE DIA (IN)	STL GA			
30.0'		5.00"	11 (.119)			
BASE PLATE DIMENSIONS						
BOLT CIRCLE DIA. (IN)	BASE PLATE (IN)	A/B HOLE WD (IN)	BASE PLATE THK (IN)			
RS3R	9.71-12.06"	11.00 SQ	1.13"	1.00"		
ANCHOR BOLT DIMENSIONS						
ANCHOR BOLT DIA (IN)	ANCHOR BOLT LENGTH (IN)					
1.00"	36.00"					
ALLOWABLE WIND LOAD (SQ. FT)						
WIND	INDICATED EPA	100 MPH	110MPH	120MPH	130MPH	140MPH
EPA	---	2.7	1.2	0.1	NA	NA

3.00 X 5.00
HAND HOLE
W/COVER

REMOVABLE
BASE COVER



3.00 X 5.00 HAND HOLE COVER 11.00 X 11.00 X 1.00 THK BASE PLATE



DESIGN	DATE
PRM	6.4.26
DRAWN	DATE
PRM	6.4.26
CHECKED	DATE
APPROVED	DATE

SOLIDWORKS DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

DECIMALS	ANGLE
X.X = ±0.030	X.X = ±1.0°
X.XX = ±0.010	X.XX = ±0.5°
X.XXX = ±0.005	
X.XXXX = ±0.0005	
FRACTION = ±1/32	

SURFACE FINISH 125/

PAINT TO ORDER

MATERIAL #: STEEL
MATERIAL:
MATERIAL SIZE:

TECHLIGHT®
WWW.TECHLIGHT.COM




THE INFORMATION CONTAINED IN THIS DRAWING
IS THE SOLE PROPERTY OF TECHLIGHTUSA.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE
WRITTEN PERMISSION OF TECHLIGHTUSA IS PROHIBITED.

DESCRIPTION


RSP 30 5 11

MASS PROPERTIES	SURFACE AREA	VOLUME	WEIGHT
DENSITY			
lbs/cu.in.	sq.in.	cu.in.	lbs
AMOUNT OF PAINT	SIZE	PART NO.	REV.
lbs	A	RSP 30 5 11	-
DO NOT SCALE DRAWING	SCALE	CAD FILE	SHEET
	1:96	RTP20 Assy	1 OF 2

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	REVD WIDTH OF COVER	5/12/2025	PRM
	B	REVD BENDS, SCREW TITLE BLK DESCRIPTION	6/4/2026	PRM



TACK
ALL 4
CORNERS



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	PPBCRSP5-11-3	BASE PLATE COVER - RMA063	2
2	P838HWHSMS	SCREW 8-15 X 3/8 HWH SS 18-8	4

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
WWW.TECHLIGHTUSA.COM ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
WWW.TECHLIGHTUSA.COM IS
PROHIBITED.

		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		NAME	DATE	TECHLIGHT.COM		
			CREATED		5.12.25			
			CHECKED					
			ENG APPR.					
			MFG APPR.					
		MATERIAL		Q.A.		COVER BASE PLATE PPBCRSP5-11 ALUM		
		RMA063	CONFIGURATION					
		FINISH						
NEXT ASSY	USED ON	PAINT TO ORDER						
APPLICATION		DO NOT SCALE DRAWING						
			SIZE		DWG. NO.	REV.		
			A		PPBCRSP5-11	B		
			SCALE:1:4		WEIGHT:	SHEET 2 OF 2		