




DRILLED PER FIXTURE REQUIREMENTS:
DM1-DRILLED FOR 1 FIXTURE
DM290-DM2180-DRILLED FOR 2 FIXTURES AT 90° OR 180°
DM390-DM3120-DRILLED FOR 3 FIXTURES AT 90° OR 120°
D490-DRILLED FOR 4 FIXTURES



3X5 HAND HOLE
STD SIDE A

DRILLED MOUNT OPTIONS


Drilling Locations

Sides	A	B	C	D
Hand Hole	X			
DM1	X			
DM290	X	X		
DM2180		X		X
DM390	X	X		X
DM490	X	X	X	X

POLE SQ

POLE HEIGHT


POLE DETAIL




TENON MOUNT OPTIONS

TENON MOUNT OPTIONS:
T238-Ø 2.38OD X 4.00 LG
T278-Ø 2.88OD X 4.00 LG
T300-Ø 3.00 OD X 6.00 LG
T312-Ø 3.50 OD X 6.00 LG

TLGFIA STD MNT
12" ABOVE HH



TLGFIA STD MOUNT



Ø0.75 x 18.00 ANCHOR BOLT
AB KIT REQ'D KAB3418G75R

POLE SPECIFICATIONS SSP15-3-11						
NO.	COMPONENT	ASTM SPEC	MIN. YIELD (PSI)			
1	POLE SHAFT	A500 GR C	50,000			
2	BASE PLATE	A36	36,000			
3	ANCHOR BOLTS	F1554 GR 55	55,000			
4	ANCHOR BOLT HDW	A153	---			
FINISH SPECIFICATIONS						
IF GALV FINISH OPTION IS SPECIFIED POLE WILL BE HOT DIP GALVANIZED						
PER ASTM A123 SPECIFICATIONS. IF GALVP FINISH OPTION IS SPECIFIED						
POLE WILL BE HOT DIP GALVANIZED PER ASTM A123, THEN POWDER COATED						
WITH TEXTURED POLYESTER POWDER COAT ELECTROSTATICALLY APPLIED.						
IF POLYESTER POWDER COAT PAINT FINISH IS SPECIFIED POLE WILL BE SHOT						
BLASTED, WASHED, PRETREATED & DRIED THEN POWDER COAT WILL BE						
ELECTROSTATICALLY APPLIED PER AAMA 2604/2605 SPECIFICATIONS.						
POLE DIMENSIONS						
POLE HGT. (FT)		POLE DIA (IN)	STL GA			
	15.0 '	3.00"	11 (.119)			
BASE PLATE DIMENSIONS						
BOLT CIRCLE DIA. (IN)		BASE PLATE (IN)	A/B HOLE WD (IN)	BASE PLATE THK (IN)		
SQP3	6.75-7.75"	7.25 SQ	0.875"	0.75"		
ANCHOR BOLT DIMENSIONS						
ANCHOR BOLT DIA (IN)		ANCHOR BOLT LENGTH (IN)				
	0.75"	18.00"				
	ALLOWABLE WIND LOAD (SQ. FT)					
WIND	INDICATED EPA	100 MPH	110MPH	120MPH	130MPH	140MPH
EPA	---	6.0	4.6	3.4	2.5	1.8


3.00 X 5.00
HAND HOLE
W/COVER

REMOVABLE
BASE COVER



3.00 X 5.00 HAND HOLE COVER

7.25 X 7.25 X .75 THK BASE PLATE



DESIGN	DATE
PRM	7.6.26
DRAWN	DATE
PRM	7.6.26
CHECKED	DATE
APPROVED	DATE

SOLIDWORKS DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

DECIMALS
X.X = ±0.030
X.XX = ±0.010
X.XXX = ±0.005
X.XXXX = ±0.0005
FRACTION = ±1/32

ANGLE
X.X = ±1.0°
X.XX = ±0.5°
SURFACE 125/
FINISH

FINISH

PAINT TO ORDER

MATERIAL #: STEEL

MATERIAL:

MATERIAL SIZE:

TECHLIGHT®

WWW.TECHLIGHT.COM

THE INFORMATION CONTAINED IN THIS DRAWING
IS THE SOLE PROPERTY OF TECHLIGHTUSA.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE
WRITTEN PERMISSION OF TECHLIGHTUSA IS PROHIBITED.

DESCRIPTION

SSP 15 3 11

MASS PROPERTIES
DENSITY

lbs/cu.in.

AMOUNT OF PAINT

lbs

DO NOT SCALE DRAWING

SCALE

1:96

CAD FILE

RTP20 Assy

SURFACE AREA

sq.in.

VOLUME

cu.in.

WEIGHT




lbs

REV.

-

SSP 15 3 11

SHEET 1 OF 2



REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	REVD SCREW DESCRIPTION	7/6/2026	PRM

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	PP3BC	BASE PLATE COVER - RMA063	2
2	P838HWHSMS	SCREW 8-15 X 3/8 HWH SS 18-8	4

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WWW.TECHLIGHTUSA.COM ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF WWW.TECHLIGHTUSA.COM IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		NAME	DATE	TECHLIGHT.COM
CREATED	6.20.25	CHECKED		
ENG APPR.		MFG APPR.		
G.A.		CONFIGURATION		
MATERIAL RMA063				
FINISH PAINT TO ORDER				
APPLICATION	DO NOT SCALE DRAWING			

SIZE A	DWG. NO. P3BC	REV. A
SCALE: 1:4	WEIGHT:	SHEET 2 OF 2