




DRILLED PER FIXTURE REQUIREMENTS:
DM1-DRILLED FOR 1 FIXTURE
DM290 -DM2180-DRILLED FOR 2 FIXTURES AT 90° OR 180°
DM390-DM3120-DRILLED FOR 3 FIXTURES AT 90° OR 120°
D490-DRILLED FOR 4 FIXTURES



3X5 HAND HOLE
STD SIDE A


DRILLED MOUNT OPTIONS

Drilling Locations

Sides	A	B	C	D
Hand Hole	X			
DM1	X			
DM290	X	X		
DM2180		X		X
DM390	X	X		X
DM490	X	X	X	X

POLE SQ


POLE HEIGHT




TENON MOUNT OPTIONS:
T238-Ø 2.38OD X 4.00 LG
T278-Ø 2.88OD X 4.00 LG
T300-Ø 3.00 OD X 6.00 LG
T312-Ø 3.50 OD X 6.00 LG

TENON MOUNT OPTIONS

TLGFIA STD MNT
12" ABOVE HH



TLGFIA STD MOUNT



Ø0.75 x 18.00 ANCHOR BOLT
AB KIT REQ'D KAB3418G75R

POLE DETAIL


3.00 X 5.00
HAND HOLE
W/COVER

REMOVABLE
BASE COVER



3.00 X 5.00 HAND HOLE COVER

8.00 X 8.00 X .75 THK BASE PLATE



POLE SPECIFICATIONS SSP20-4-11

NO.	COMPONENT	ASTM SPEC	MIN. YIELD (PSI)			
1	POLE SHAFT	A500 GR C	50,000			
2	BASE PLATE	A36	36,000			
3	ANCHOR BOLTS	F1554 GR 55	55,000			
4	ANCHOR BOLT HDW	A153	---			

FINISH SPECIFICATIONS

IF GALV FINISH OPTION IS SPECIFIED POLE WILL BE HOT DIP GALVANIZED

PER ASTM A123 SPECIFICATIONS. IF GALVP FINISH OPTION IS SPECIFIED

POLE WILL BE HOT DIP GALVANIZED PER ASTM A123, THEN POWDER COATED

WITH TEXTURED POLYESTER POWDER COAT ELECTROSTATICALLY APPLIED.

IF POLYESTER POWDER COAT PAINT FINISH IS SPECIFIED POLE WILL BE SHOT

BLASTED, WASHED, PRETREATED & DRIED THEN POWDER COAT WILL BE

ELECTROSTATICALLY APPLIED PER AAMA 2604/2605 SPECIFICATIONS.

POLE DIMENSIONS

POLE HGT. (FT)	POLE DIA (IN)	STL GA			
20.0'	4.00"	11 (.119)			

BASE PLATE DIMENSIONS

BOLT CIRCLE DIA. (IN)	BASE PLATE (IN)	A/B HOLE WD (IN)	BASE PLATE THK (IN)		
P4875 7.25-8.75"	8.00 SQ	1.00"	0.75"		

ANCHOR BOLT DIMENSIONS

ANCHOR BOLT DIA (IN)	ANCHOR BOLT LENGTH (IN)				
0.75"	18.00"				

ALLOWABLE WIND LOAD (SQ. FT)

WIND	INDICATED EPA	100 MPH	110MPH	120MPH	130MPH	140MPH
EPA	---	6.6	4.7	3.2	2.1	1.2

DESIGN	DATE
PRM	7.7.26
DRAWN	DATE
PRM	7.7.26
CHECKED	DATE
APPROVED	DATE

SOLIDWORKS DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

DECIMALS
X.X = ±0.030
X.XX = ±0.010
X.XXX = ±0.005
X.XXXX = ±0.0005
FRACTION = ±1/32

ANGLE
X.X = ±1.0°
X.XX = ±0.5°

SURFACE 125/
FINISH

FINISH

PAINT TO ORDER

MATERIAL #: STEEL

MATERIAL:

MATERIAL SIZE:

TECHLIGHT[®]

WWW.TECHLIGHT.COM

THE INFORMATION CONTAINED IN THIS DRAWING
IS THE SOLE PROPERTY OF TECHLIGHTUSA.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE
WRITTEN PERMISSION OF TECHLIGHTUSA IS PROHIBITED.

DESCRIPTION

SSP 20 4 11

MASS PROPERTIES
DENSITY

lbs/cu.in.

AMOUNT OF PAINT

lbs

DO NOT SCALE DRAWING

SCALE

1:96

CAD FILE

RTP20 Assy

SURFACE AREA

sq.in.

VOLUME

cu.in.

WEIGHT

lbs

REV.

-



PART NO.

SSP 20 4 11


SHEET

1 OF

2



REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	REVD BENDS, SCREW & TITLE BLK DESCRIPT	6/3/2026	PRM



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	PBC4SQ9SQ4H	BASE PLATE COVER - RMA063	2
2	P838HWHSMS	SCREW 8-15 X 3/8 HWH SS 18-8	4

		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±	NAME		DATE		TECHLIGHT.COM		
			CREATED		6.27.25				
			CHECKED				COVER BASE PLATE PBC4SQ9SQ4H ALUM		
			ENG APPR.						
			MFG APPR.						
		G.A.							
		CONFIGURATION							
		MATERIAL	RMA063						
		FINISH	PAINT TO ORDER						
NEXT ASSY	USED ON								
APPLICATION		DO NOT SCALE DRAWING							

SIZE	DWG. NO.				REV.
A	PBC4SQ9SQ4H				A
SCALE: 1:4		WEIGHT:			SHEET 2 OF 2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
WWW.TECHLIGHTUSA.COM ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
WWW.TECHLIGHTUSA.COM IS
PROHIBITED.