



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

FEATURES — Fully gasketed, corrosion-resistant housing. Energy-efficient LED technology. EZ snap-out chevron direction indicators. UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

CONSTRUCTION — Corrosion-resistant, polycarbonate UV-stabilized housing. Removable KO directional indicators. Single face only. Polycarbonate face plate.

ELECTRICAL SYSTEM — Dual 120V/277V voltage. Charge rate/power “ON” LED indicator light and push-to-test switch for mandated code compliance testing. LVD (low voltage disconnect) prevents battery from deep discharge. Long-life, maintenance-free, rechargeable NiCd battery (B Model). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.


MOUNTING — Knockouts for back mounting.

ILLUMINATION — High-performance smooth thermoplastic reflector and plastic lens for optimal light distribution. Ultra-bright, energy efficient, long-life Red or Green LED (exit sign illumination). 6" EXIT letters.

WARRANTY — Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.



Wet Location LED Exit Sign WLE SERIES



Series	Housing Height	Length & Width
WLE	11.75"	11.75" x 3.75"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **WLERB**

WLE			
Series	Letter Color	Battery	Options
WLE	R Red G Green	Blank AC Only B Battery Back-Up	HT Internal Heater